## **HV301G Applications**

### Interior

- Acoustical ceiling installation
- Drywall installation
- Squaring/layout
- Raised access flooring
- Interior finishing work
- Reference marks
- Leveling
- Vertical alignment
- Plumb
- Small-to-medium commercial construction



## Multipurpose Green Beam Construction Laser for Interior Applications

# Tough, High Visibility, Versatile Interior Construction Laser

The automatic, self-leveling Spectra Precision® HV301G offers exceptional versatility and superior green beam visibility for increased productivity at a great value. The HV301G laser handles a wide variety of horizontal, vertical and plumb applications.

The HV301G green laser beam is easy to see in all interior jobsite conditions. The superior visibility of the green beam is useful for extended ranges or in bright conditions. The beam stays visible for efficient work in less than ideal conditions.

The HV301G laser transmitter sends a continuous, self-leveled 360-degree laser reference over the entire work area. Various rotation speeds and scanning angles allow you to concentrate the laser beam in your work area for optimum visibility. A 90-degree reference beam is included for a wide variety of layout work and point transfer. A 360 degree remote control allows operation of key functions over the jobsite.

Designed to be used by any contractor, the HV301G laser is easy to set up and use. Intuitive controls allow operators to carry out many functions with simple "one-touch" commands.

Electronic automatic self-leveling in both horizontal and vertical modes assure accuracy. A height of instrument alert turns the beam off when the elevation of the laser changes or is disturbed. The laser can also be used in the manual leveling mode for slope applications such as matching existing ceiling slopes.

Vertical applications are as easy to set up as horizontal applications. No additional vertical mounting brackets or trivets are necessary.

Simply setup the laser on the built-in no-slip rubber footpads or mount vertically to a tripod with the built-in tripod mount.

The HV301G is rugged enough for the toughest jobsite. Highly durable construction enables the HV301G laser to survive a drop of up to 3 feet (1 meter) onto concrete. IP54 sealing assures the laser is unaffected by dust or moisture.

The performance of the Spectra Precision 300 series has been proven reliable in tens of thousands of units sold and working throughout the world.

#### The HV301G Laser Package includes:

- HV301G Laser
- 360-degree IR remote control
- Rechargeable NiMH batteries and charger
- · Universal wall, floor, and tripod mount
- Enhanced ceiling target
- Green laser glasses
- Multi-Language operator's manual
- · Hard carrying case

Optional universal receivers are available.





## **Spectra Precision HV301G**

## Maximum Visibility and Versatility in Interior Construction Applications



#### **HV301G Laser Features & Benefits**

- · High visibility green beam is four times more visible than standard red beam lasers allowing you to work longer distances and in brighter
- Automatic self-leveling in horizontal and vertical applications assures accuracy and quick setups
- Temperature compensation for accurate use throughout the day
- · Intuitive, one-touch operator controls allow anyone to get to work quickly
- Adjustable rotation speeds and scanning zones position the beam where it is needed
- · Height of Instrument alert turns off laser and alerts the operator if elevation is changed to avoid erroneous readings
- Remote control allows all functions to be carried out from anywhere on the jobsite
- Flexible power options efficient Nickel-Metal Hydride batteries are standard; alkaline batteries can provide power backup
- Removable rotor cage for precise pointing and 360° coverage
- High durability design can withstand 3 ft (1m) drops onto concrete reducing downtime and repair costs
- IP54 sealing allows work in all environments
- Built-in vertical stand and 5/8"×11" horizontal and vertical mounting
- Marking notches on each side of the unit provides operator fast positioning over a point for plumb transfer
- Single axis manual slope mode to match known references
- · Proven performance, ruggedness, and reliability with tens of thousands of 300 series lasers in the field
- Choice of optional universal receivers for exterior leveling tasks (works with visible green and red beam lasers and infrared lasers)

#### **HV301G Laser Specifications**

Laser type	532 nm Green Beam
Laser class	Class 3R / IIIa, <5mW
Laser accuracy ±3/	32 in at 100 ft (±2.2 mm at 30 m, ±15 arc seconds)
Interior range	up to 250 ft (75 m)
	ion Yes (2 arc seconds / °C)
Self-leveling range	±5 degrees
Compensation method	Electronic self-leveling
	'D' size NiMH batteries standard (Alkaline optional)
Battery life	18 hours rechargeable, 45 hours alkaline
	Flashing red LED
	Less than 10 hours
Rotation speed	0/10/80/200/600 rpm
Scanning angles	Four preset angles 8°/45°/90°/180°
Operating temperature	32 °F to 104 °F (0 °C to 40 °C)
Storage temperature	4 °F to 158 °F (-20 °C to 70 °C)
	Yes, and IP54 sealing
Size	. 9.6L × 6.5W × 7.3H in 2 (4.5L × 16.5W × 18.5H cm)
Weight	6 lbs (2.7 kg)
	2 years



High visibility green ceiling target



RC601 Remote Control included - Long range 250 ft (75 m) use

M300

Universal Mount







### **HL750U Laserometer Specifications**

Reception Height	5.0 inches (127 mm)
On Grade Sensitivity 1/32, 1/16, 1/8, 1/4	4, 1/2 in (.5, 1, 2, 5, 10 mm)
Operating Range (radius)	825 ft (250 m)
Warranty	

#### **HR150U Receiver Specifications**

Reception Height	2.0 inches (50 mm)
On Grade Sensitivity	1/8 in (3 mm)
Operating Range (radius)	500 ft (150 m)
Warranty	1 Year

NORTH & LATIN AMERICA Trimble Construction Tools Division 5475 Kellenburger Road • Dayton, Ohio 45424 • USA 800-538-7800 (Toll Free) +1-937-245-5154 Phone • +1-937-233-9441 Fax

EUROPE

Trimble GmbH

Am Prime Parc 11 • 65479 Raunheim • GERMANY +49-6142-2100-0 Phone • +49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation Singapore Pty Limited 80 Marine Parade Road • #22-06, Parkway Parade • Singapore 449269 • +65-6348-2212 Phone • +65-6348-2232 Fax

YOUR LOCAL SPECTRA PRECISION REPRESENTATIVE





www.trimble.com/spectra