Trimble TDC600

HANDHELD



KEY FEATURES

- All-in-one GNSS data collector and smartphone
- ► Android[™] 8.0 operating system
- ► 6-inch high resolution sunlight-readable display
- Powerful Qualcomm[®] processor with 4 GB RAM and 64 GB internal storage
- Large capacity, user replaceable all day battery
- Real-time positioning with built-in GNSS receiver
- Google Mobile Services certified with access to Google Play™ store apps
- Ultra-rugged design with MIL-STD-810G certification
- 4G LTE, Wi-Fi, Bluetooth® connectivity options for voice calls and data
- Ergonomic, lightweight and slim form factor
- Front- and rear-facing cameras
- Supports the Trimble[®] Catalyst[™] service and Trimble R Series GNSS receivers
- Runs Trimble TerraFlex[™], Trimble Access[™], third-party or custom-developed field applications

Learn more: www.SITECHnorcal.com



STANDARD FEATURES

SYSTEM

- Integrated 4G cellular data, text and voice capability
- 5 MP front camera and 13 MP rear camera
- Wi-Fi IEEE 802.11 a/b/g/n/ac, 2.4 GHz / 5 GHz dual-band
- 6.0 inch LED-backlight screen with capacitive multi-touch
- Long-life user replaceable Li-lon battery
- 2.2 GHz Qualcomm Snapdragon™ 626 processor
- 4 GB RAM
- · 64 GB flash memory¹
- · 1 MicroSDHC memory card slot
- · Integrated speaker and microphone

OPERATING SYSTEM

- Android 8.0 (Oreo)
- Languages available: Afrikaans, Azebaijani, Bulgarian, Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hindi, Hungarian, Italian, Korean, Lithuanian, Norwegian (Bokmål), Polish, Portuguese (Portugal and Brazil), Romanian, Russian, Serbian (Cyrillic), Simplified Chinese, Spanish, Swedish, Turkish
- · Software package includes: Google Mobile Services

COMMUNICATIONS²

- Cellular: GSM (850/900/1800/1900), WCDMA (B1/B2/B5/B8), LTE-FDD (B1/B2/ B3/B4/B5/B7/B8/B12/B13/B17/B20/B25/B28), LTE-TDD (B38/B39/B40/B41), TD-SCDMA (B34/B39)
- Wi-Fi IEEE 802.11 a/b/g/n/ac
- Bluetooth 4.1
- NanoSIM x 2
- USB 3.0 (Type-C)
- NFC

STANDARD ACCESSORIES

- Hand strap
- A/C charger
- · USB cable
- Lanyard

OPTIONAL ACCESSORIES

- · External magnetic GPS antenna
- Pole bracket
- · Replacement batteries

SOFTWARE COMPATIBILITY

Please refer to the Product Compatibility matrix (www.trimble.com/mappingGIS/productcompatibility)

- 1. The actual available capacity of the internal memory is less than the specified capacity because the operating system and default applications occupy part of the memory. The available capacity may change when you upgrade applications or the device.

 2. Bluetooth, wireless LAN and cellular type approvals are country specific. Trimble TDC600 handheld has Bluetooth, wireless LAN and cellular approval in North America (excluding Verizon) and EU. For other countries, please consult your local Reseller.

 3. Horizontal Root Mean Squared accuracy, Requires data to be collected using vertical mounting, minimum of 4 satellites, PDOP mask at 99, SNR mask at 12 dBHz, elevation mask at 5 degrees, and reasonable multipath conditions, lonospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception.

 4. SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS available in Japan only.

Specifications subject to change without notice

Trimble TDC600 HANDHELD

++++++++++++++++

TECHNICAL SPECIFICATIONS

PHYSICAL

	. 196 mm x 93.4 mm x 17.2 mm (7.7 in x 3.6 in x 0.67 in)
Processor	Qualcomm Snapdragon 626, Octa-core, Clock frequency: 2.2 GHz
Memory	4 GB RAM
	64 GB
User Interface Keyboard	2 volume keys, power key
4 progra	ammable keys, standard Android touch panel 3 buttons,
	On screen keyboard
Battery	Li-lon removable battery
	Standard capacity 8000 mAh
Battery life	15 hours @ 20° C with GPS on
Charging time	
END/IDONA/ENITAL	

ENVIRONMENTAL

Temperature	
Operating	-20 °C to +55 °C (-4 °F to +131 °F)
Storage	
Humidity	95% non-condensing
Water & Dust proof	IP67
Free drop	1.2 m (MIL-STD-810G)

Display...... Gorilla Glass 3, Optically bonded, AF coated, auto rotate

INPUT/OUTPUT Expansion......MicroSDHC memory card (up to 256 GB)

Resolution
Brightness 500 Cd/m²
Audio
Audio jack through USB-C
Pogo pin connector
I/O USB 3.0, external antenna connector
Digital camera
Rear camera
Front camera
Sensors
compass, gyrometer, accelerometer, barometer

GNSS

GNSS Receiver	U-blox Neo-
M8T Internal antenna: 72 channels.	GPS L1 C/A, GLONASS, BeiDou,
SBAS Integrated real-time	SBAS (WAAS/EGNOS/MSAS/
GAGAN/QZSS) Tri constellation sys	stem GPS/GAL, GPS/GLO/GAL or
	GPS/BeiDou/GAL External antenna
connector	Yes
Protocol	Location Services

ACCURACY SPECIFICATIONS (HORIZONTAL RMS)	
Real-time SBAS ⁴	<1.5 m typica



NMEA output (optional)



SITECH NorCal 833 Montague Ave. San Leandro, CA 94577

www.SITECHnorcal.com





SITECH Oregon 21505 Bents Court NE Aurora, OR 97002 www.SITECHoregon.com





NORTH AMERICA

Trimble Inc. 10368 Westmoor Dr Westminster CO 80021 USA

EUROPE

Trimble Germany GmbH Am Prime Parc 11 65479 Raunheim **GERMANY**

ASIA-PACIFIC

Trimble Navigation Singapore PTE Limited 3 HarbourFront Place #13-02 HarbourFront Tower Two Singapore 099254 SINGAPORE

© 2019–2020, Trimble Inc. All rights reserved. Trimble, and the Globe & Triangle logo are trademarks of Trimble Inc., registered in the United States and in other countries. Access, Catalyst and TerraFlex are trademarks of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. Android, Google and Google Play are trademarks of Google LLC. All other trademarks are the property of their respective owners. PN 022516-439D (07/20)

